



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

The system architecture for renewable synthetic fuels

Ridjan, Iva

Publication date:
2013

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Ridjan, I. (2013). *The system architecture for renewable synthetic fuels*. Poster presented at Workshop on Electrolysis and CO₂-recycling, Roskilde, Denmark.
<http://indico.conferences.dtu.dk/getFile.py/access?resId=0&materialId=6&confId=131>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

THE SYSTEM ARCHITECTURE FOR RENEWABLE SYNTHETIC FUELS



Iva Ridjan,
supervised by Brian Vad Mathiesen
iva@plan.aau.dk


DEPARTMENT OF DEVELOPMENT AND PLANNING, SUSTAINABLE ENERGY PLANNING RESEARCH GROUP



To overcome and eventually eliminate the existing heavy fossil fuels in the transport sector, there is a need for new renewable fuels. This transition could lead to large capital costs for implementing the new solutions and a long time frame for establishing the new infrastructure unless a suitable infrastructure is present. The system integration of synthetic fuels will therefore depend on the existing infrastructure and the possibility of continuing its exploitation to minimize the costs and maximize the use of the current infrastructure in place. The production process includes different steps and production plants, so it is important to implement it in the best manner possible to ensure an efficient and flexible system. The poster will provide an overview of the steps involved in the production of synthetic fuel and possible solutions for the system architecture based on the current literature and best practice.

PRODUCTION CYCLE OF SYNTHETIC FUELS AND PROPOSED PATHWAYS


In order to evaluate the potential of electrolyzers for liquid fuel production, the knowledge on individual stages of production cycle and technology implemented is important.




Three proposed pathways:

- Biomass hydrogenation
- CO₂ hydrogenation
- Co-electrolysis

BIOMASS HYDROGENATION





The principal objective in this pathway is to create a liquid fuel from biomass, which is boosted by hydrogen from steam electrolysis. In this way, the energy potential of the biomass resource is maximized.




CO₂ HYDROGENATION


This pathway combines carbon dioxide and hydrogen gases together in form of syngas, which is thereafter converted by chemical synthesis to fuel.



CO-ELECTROLYSIS



This pathway combines steam and CO₂ electrolysis into a process called co-electrolysis, and the produced synthetic gas can afterwards be catalysed into various types of fuel.




SYSTEM ARCHITECTURE

Two proposed systems:

- Centralized – big scale production plants and high electrolyser capacities
- Decentralized – smaller production plants, possible local optimization

Key principles:

- One large grid solution is preferred (local smaller grids could be needed)
- Transportation of electricity is first priority followed by transportation of CO₂, syngas or hydrogen
- The capture of carbon from air using synthetic trees is excluded from the analysis because it is more expensive solution at the moment - small difference in the electricity needed for CO₂ extraction compared to stationary CCR.



Decentralized and centralized solution for utilizing renewable fuels biomass gasification pathway and combined cycle



CO₂ hydrogenation and co-electrolysis possible system structure

CONCLUSION/FUTURE WORK

The work to date indicates that there are a lot of possible solutions that need to be further investigated to clarify some insecurity related to different production steps. During the research, it became apparent that the true benefits of each system structure cannot be determined without a detailed understanding of the most likely technologies to be used in the future.

The biomass gasification pathway infrastructure could be defined by possibility and costs of syngas transportation and chemical synthesis losses, while CO₂ recycling pathways structure will be defined by distributed nature of future carbon sources as well as process heat losses of chemical synthesis.

The chosen fuels are going to depend on the engine efficiencies, driving range and driving efficiency of methane and methanol/DME vehicles. Future research will therefore orient more in the detailed analysis of the end use of the produced fuels.